

LUXURY OAK

PRODUCT SPECIFICATIONS

Type	European Oak	Style	Single Plank
Description	Engineered multi-layer natural timber veneer interlocking floor boards featuring G5 Locking System		
Board Construction	3mm hardwood face layer 11mm thick plywood mixed with Poplar and Eucalyptus (bottom layer is Poplar)		
Installation Method	Direct Stick or Floating	Finish	Light Wire Brush
Coating	7 Coats of Treffert Lacquer combined with wire brush and colour stain, 4 Base Coats, 1 Coat of Abrasive Resistance Coating and 2 Coats of Top Coat		
Profile	0.6mm Bevel on two sides and square on end join	Underlay	Standard - 2mm Closed Cell Foam Acoustic - 3mm or 5mm ImpactaMat
Dimensions	1860 x 189 x 14mm	Boards per Pack	8
m² per Pack	2.812m ²	m² per Pallet	112.48m ²
Pack Weight	12kg	Timber Grade	ABCD

TEST DATA

Fire Rating	Critical Heat Flux: 4.2kW/m ² Smoke Value: 8% minute	Slip Resistance	P2
Janka Rating	6	Certification	Forestry Stewardship Certification (FSC)

Warranty	25 Year Residential Warranty 10 Year Commercial Warranty		
Variations in Timber	<p>Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.</p> <p>Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.</p>		