

TIMBER HYBRID

PRODUCT SPECIFICATIONS

Type	Timber Hybrid	Style	Single Plank
Description	Stone Polymer Composite flooring featuring Valinge 5Gi Locking System		
Installation Method	Floating	Profile	Mirco-Bevel
Coating	Factory coated with seven layers of UV cured acrylic	Finish	Matt Brushed <8%
Underlay	1.5mm high density closed cell foam underlay pre-attached	Timber Grade	ABCD
	Australian Timber		European Oak
Dimensions	1830 x 136 x 7.5mm		1830 x 190 x 7.5mm
Timber Veneer	0.6mm		1.2mm
Boards per Pack	8		6
m² per Pack	1.991m ²		2.086m ²
m² per Pallet	139.373m ²		146.034m ²
Pack Weight	23.5kg		24.5kg

TEST DATA

Janka Rating	6 - 11	Certification	Forestry Stewardship Certification (FSC)
---------------------	--------	----------------------	--

Warranty	25 Year Residential Warranty 10 Year Commercial Warranty
Variations in Timber	<p>Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species.</p> <p>Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour.</p>